



3 Year/1500 hours warranty.



FEATURES

- 50°C temperature rating
- ComApMRS16controller
- Enclosed Silenced Canopy
- Powder coated finish
- Fork Points and centre liftinglug
- Schneider Breakers
- 110% double bundled base
- Emergency E stop
- Australian Compliant Wiring and M.E.N link
- Remote Start and ATS feature
- Site safe lockable canopy
- Pricing includes commissioning and pre delivery run in

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010

OPTIONAL UPGRADES

Fire extinguisher
battery & starter Isolator
Solar battery charger
3-way fuel valve
ComAp cell phone monitoring

WARRANTY

3 year – 1500 hour

Prime power (prp) Prime power is available for an unlimited number of annual hours in variable load application, in accordance with gb/t2820-97 eqv iso8528; a 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby power rating (esp) The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

GEN 22KT

Silent Diesel Generator



ENGINE DATA

Make & Model	Kubota V2203	
Type	Water Cooled, Nature Aspirate Engine	
Output Rating	Ps/Rpm	23.4/1500
	Kw/Min	17.2/1500
Bore X Stroke	Mm	87 X 92.4mm
Position Displacement	L	2.197
Fuel Type	Diesel	
Fuel Consumption (Based On 75% Full Load)	L/H	3.85
Lube Oil Pump Capacity	L	9.7
Coolant Capacity	L	8.1
Battery X Quantity	1 X 80Ah	
Fuel Tank Capacity	L	145

ALTERNATOR DATA

Alternator	Stamford S0L2-G	
Frequency	(Hz)	50
Output Rating	Continuous (KVA)	20
	Standby (KVA)	22
No. of Phase	3Phase, 4Wire	
Rated Voltage	V	240/415
Power Factor	0.8	
Voltage Regulation	%	+1
Excitation	Self Exciting	
Insulation	Class H	

SOUND

Sound Level	7m dB(A)	63
-------------	----------	----

DIMENSIONS

Dimensions	Length (mm)	2000
	Width (mm)	900
	Height (mm)	1230
Dry weight	Kg	950