

Model GEN145CT



DIESEL GENERATING SET 400/230 V - 50 Hz - 3 Phase

MODEL		GEN145CT	
Power Pf.0.8	Standby	kVA	145
		kW	116
	Prime	kVA	132
		kW	105.6

ENGINE

CUMMINS				
Model	6BTAA5.9G2			
Engine Power Output	kWm	130		
at rated rpm	HP	174		
Aspiration and Cooling		Turbocharged and Charge Air Cooled		
Total Displacement	Litre	5.9		
No. of Cylinders and Build		6 - Inline		
Engine Speed	rpm	1500		
Bore and Stroke	mmxmm	102x120		
Compression Ratio		17.3:1		
Governor		Electronic		
Fuel Consumption at full load	L/hr	30		
Fuel Tank Capacity	Litre	800		
Oil Capacity	Litre	16.4		
Coolant Capacity	Litre	54		
Radiator Cooling Air	m³/min	148		
Air Intake - Engine	m³/min	7.2		
Exhaust Gas Flow	m³/min	19.68		

ALTERNATOR UCI274E

Design	Brushless single bearing, revolving field	
Stator	2/3 pitch	
Rotor	Single bearing, flexible disc	
Insulation System	Class H	
Standard Temperature Rise	125 - 163°C Continuous	
Exciter Type	Self Excited	
Phase Rotation	A (U), B (V), C (W)	
Alternator Cooling	Direct drive centrifugal blower fan	
AC Waveform Total Harmonic Distortion	No load < 1.5%. Non distorting balanced linear load < 5%	
Telephone Influence Factor (TIF)	<50 per NEMA MG1-22.43	
Telephone Harmonic Factor (THF)	<2%	



DIMENSIONS

SOUND ATTENUATED TYPE			
DIMENSIONS (L x W x H)	mm	3440x1156x2278	
DRY WEIGHT	kg	2525	

WARRANTY

Blue Diamond Warranty		2 year
Cummins engine warranty	Prime power	12 months - unlimited hours
	Standby power	2 years - 500 hours